

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: SUPERLIFE 316
PRODUCT CODE: 10-0747-XX

HMIS CODES H F R P
1 0 0 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: BURKE INDUSTRIAL COATINGS
ADDRESS: 600 S. 74th Place, Suite 108, Ridgefield, WA 98642
EMERGENCY PHONE: (800) 255-3924 INFORMATION PHONE: (360)887-8819
(CHEM-TEL)
EFFECTIVE DATE: 9-1-07 NAME OF PREPARER: DARRELL BADERTSCHER

SECTION II - HAZARDOUS INGREDIENTS
SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mm HG @ TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLV	OTHER		
TEXANOL ESTER ALCOHOL	25265-77-4	N/A	N/A		0.0 68F	<5.0%

***NO TOXIC CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR ARE PRESENT**

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: ESTIMATED 212 F SPECIFIC GRAVITY (H2O=1): 1.4
VAPOR DENSITY: LIGHTER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 0.33 LB/GL (39 G/L)
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: OPAQUE COATING, SWEET SMELL

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A METHOD USED: CLOSED CUP
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

USE FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS TO PROTECT FIREFIGHTERS FROM HAZARDOUS COMBUSTION PRODUCTS. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT POSSIBLE EXPLOSION.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE DUE TO BUILD UP OF STEAM WHEN EXPOSED TO EXTREME HEAT.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID N/A

INCOMPATIBILITY (MATERIALS TO AVOID): AVOID STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: POSSIBLE OXIDES OF CARBON AND NITROGEN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION OF VAPOR OR MIST CAN CAUSE THE FOLLOW: HEADACHE; NAUSEA; IRRITATION OF NOSE, THROAT AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

DIRECT CONTACT WITH MATERIAL CAN CAUSE THE FOLLOWING: SLIGHT IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE THE FOLLOWING: SLIGHT SKIN IRRITATION.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

WHILE THIS MATERIAL HAS A LOW DEGREE OF TOXICITY, INGESTION OF EXCESSIVE QUANTITIES MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT.

HEALTH HAZARDS (ACUTE AND CHRONIC)

INGESTION AND SKIN ABSORPTION: NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION. INHALATION: MAY BE IRRITATING TO MUCOUS MEMBRANES, RESPIRATORY TRACT, AND MAY PRODUCE SYMPTOMS OF HEADACHE OR NAUSEA IN POORLY VENTILATED AREAS. PROLONGED SKIN CONTACT MAY CAUSE REDDENING OF THE SKIN. DIRECT EYE CONTACT MAY CAUSE EYE IRRITATION.

CARCINOGENICITY: NTP: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO
THIS MATERIAL HAS NOT BEEN IDENTIFIED AS A CARCINOGEN BY NTP, IARC OR OSHA.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

PRE-EXISTING LUNG DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

EMERGENCY AND FIRST AID PROCEDURES

SWALLOWING: NO HARMFUL EFFECTS EXPECTED. INHALATION: NO EMERGENCY CARE ANTICIPATED. EYES AND SKIN: IMMEDIATELY FLUSH EYES WITH WATER UNTIL WATER IS NO LONGER CLOUDY. WASH SKIN WITH SOAP AND WATER UNTIL WATER IS NO LONGER CLOUDY. IF CLOTHING IS SOAKED, REMOVE AND WASH BEFORE REUSE. TOXICOLOGY STUDIES OF SIMILAR MATERIALS HAVE SHOWN VERY LOW ACUTE TOXICITY. THERE IS NO SPECIFIC ANTIDOTE. TREATMENT OF OVER EXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITION.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

RESTRICT AREA TO ONLY THOSE PERSONNEL NEEDED. MAJOR SPILLS SHOULD BE COLLECTED FOR DISPOSAL. MINOR SPILLS MAY BE FLUSHED INTO SEWER IF PERMITTED BY STATE, FEDERAL AND LOCAL REGULATIONS.

WASTE DISPOSAL METHOD

INCINERATE OR BURY IN SUITABLE LANDFILL WHERE PERMITTED BY APPROPRIATE GOVERNMENT REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP CONTAINERS COOL AND DRY. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION. KEEP PRODUCT CONTAINERS CLOSED WHEN NOT IN USE. AVOID SUBJECTING THIS PRODUCT TO EXTREME TEMPERATURE VARIATIONS AND FREEZING.

OTHER PRECAUTIONS

DO NOT STORE BELOW 40 DEGREES FAHRENHEIT.

SECTION VIII - CONTROL MEASURES**RESPIRATORY PROTECTION**

RESPIRATORY PROTECTION MAY BE NECESSARY TO MINIMIZE EXPOSURE TO VAPORS DEPENDING ON THE NATURE AND CONCENTRATION OF THE AIRBORNE MATERIAL. USE A RESPIRATOR WITH APPROPRIATE FILTERS AND CARTRIDGES (NIOSH APPROVED IF AVAILABLE) OR SUPPLIED AIR EQUIPMENT.

VENTILATION

IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE TO MINIMIZE EXPOSURE, ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED.

PROTECTIVE GLOVES

USE GLOVES MADE OF NEOPRENE, BUTYL RUBBER OR NATURAL RUBBER.

EYE PROTECTION

USE CHEMICAL SPLASH GOGGLES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER BE AVAILABLE IN THE WORK AREA FOR FLUSHING EYES AND SKIN. IMPERVIOUS CLOTHING SHOULD BE WORN AS NEEDED.

WORK/HYGIENIC PRACTICES

AFTER USING THIS PRODUCT WASH HANDS THOROUGHLY PRIOR TO EATING OR SMOKING.

SECTION IX - DISCLAIMER

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH BURKE INDUSTRIAL COATINGS OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE AND SUITABLE TO THEIR CIRCUMSTANCES. TO OUR KNOWLEDGE, THIS MSDS COMPLIES WITH 29 CFR 1910, 1200.