

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PRIMELIFE 5150
 PRODUCT CODE: 14-5150-00

HMIS CODES H F R P
 1 4 3 G

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: BURKE INDUSTRIAL COATINGS
 ADDRESS: 600 S.74th Place, Suite 108, Ridgefield, WA 98642
 EMERGENCY PHONE: (800) 255-3924 INFORMATION PHONE: (360)887-8819
 EFFECTIVE DATE: 9-1-07 NAME OF PREPARER: DARRELL BADERTSCHER

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT %
			LESS THAN
01	PROPANE	00074-98-6	20.0%
02	XYLENE	01330-20-7	15.0%
03	ACETONE	00067-64-1	15.0%
04	N-BUTANE	00106-97-8	10.0%
05	ETHYL BENZENE	00100-41-4	5.0%
06	TOLUOL	00108-88-3	5.0%
07	S-C 100 SOLVENT	64742-95-6	5.0%
08	RED IRON OXIDE	01309-37-1	5.0%
09	GLYCOL ETHER EP	02807-30-9	5.0%

-----EXPOSURE LIMITS-----

ITEM	ACGIH		OSHA		COMPANY	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	1000 ppm	N.E.	1000 ppm	N.E.	N.E.	NO
02	100 ppm	150 ppm	100 ppm	150 ppm	N.E.	YES
03	750 ppm	1000 ppm	750 ppm	1000 ppm	N.E.	YES
04	800 ppm	N.E.	800 ppm	N.E.	N.E.	NO
05	100 ppm	125 ppm	100 ppm	125 ppm	N.E.	NO
06	50 ppm	N.E.	100 ppm	150 ppm	N.E.	YES
07	N.E.	N.E.	N.E.	N.E.	N.E.	YES
08	10 mg/m3	N.E.	6 mg/m3	N.E.	N.E.	NO
09	25 ppm	N.E.	25 ppm	N.E.	N.E.	YES

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION III - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: May cause flash fire or explosion.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Allergic reactions are possible. May cause skin sensitization, and allergic reaction, which becomes evident on reexposure to this material. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed. Irritating to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Possible reproductive hazard.

PRIMARY ROUTE(S) OF ENTRY: SKIN ABSORPTION INHALATION INGESTION EYE CONTACT SKIN CONTACT

SECTION IV - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

OTHER PROTECTIVE EQUIPMENT: Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

HYGIENIC PRACTICES: No Information.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: -44 - 344 F	VAPOR DENSITY :	Is heavier than air
ODOR	ODOR THRESHOLD :	
APPEARANCE	EVAPORATION RATE:	Is faster than Ether
SOLUBILITY IN H2O		
FREEZE POINT	SPECIFIC GRAVITY:	0.1923
VAPOR PRESSURE	pH @ 0.0 % :	
PHYSICAL STATE :	VISCOSITY :	
COEFFICIENT OF WATER/OIL DISTRIBUTION:		

(see Section 16 for abbreviation legend)

SECTION X - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: No Information

INCOMPATIBILITY: No Information

HAZARDOUS DECOMPOSITION PRODUCTS: No Information

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION XII - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION XIII - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION IVX - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: No Information

SECTION XV - TRANSPORTATION INFORMATION

No transportation information is available

SECTION XVI - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD PRESSURIZED GAS HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

-----CHEMICAL NAME-----	CAS NUMBER	WT/WT % IS LESS THAN
Xylene	01330-20-7	15.0%
Acetone	00067-64-1	15.0%
Ethyl Benzene	00100-41-4	5.0%
Toluol	00108-88-3	5.0%

NEW JERSEY RIGHT-TO-KNOW:

The following material are non-hazardous, but are among the top five components in this product:

-----CHEMICAL NAME-----	CAS NUMBER
Calcium Carbonate	01317-65-3

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

-----CHEMICAL NAME-----	CAS NUMBER
Calcium Carbonate	01317-65-3
Linseed Alkyd	NA
Solid Acrylic Resin	NA

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

-----CHEMICAL NAME----- CAS NUMBER
Toluol 00108-88-3

SECTION XVII - REGULATORY INFORMATION

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulation except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION XVII - REGULATORY INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 4 REACTIVITY: 3

PREVIOUS MSDS REVISION DATE 4/8/95

LEGEND: N.A. - Not Applicable, N.E. - Not Established
N.D. - Not Determined

SECTION XVIII - DISCLAIMER

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with Burke Industrial Coatings or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. To our knowledge, this MSDS complies with 29 CFR 1910.1200