

PRODUCT NAME: TOPCOAT 1010 H.G. WHITE
 PRODUCT CODE: 20-1010-XX

HMIS CODES: H F R P
 0 0 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: BURKE INDUSTRIAL COATINGS

ADDRESS : 600 S. 74th Place, Suite 108, Ridgefield, WA 98642

EMERGENCY PHONE : (800) 255-3924 DATE PRINTED : 1-5-10
 INFORMATION PHONE : (360)887-8819 NAME OF PREPARER : DARRELL BADERTSCHER

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
-----------------------	------------	--------------------------------	-------------------

 *** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT ***

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

No information available.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: Estimate 212°F SPECIFIC GRAVITY (H2O=1): 1.21
 VAPOR DENSITY: LIGHTER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
 COATING V.O.C.: 1.79 lb/gl
 SOLUBILITY IN WATER: SOLUBLE
 APPEARANCE AND ODOR: OPAQUE COATING, SWEET SMELL

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A METHOD USED: Closed Cup
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a UPPER: n/a

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Use full protective equipment including self-contained breathing apparatus to protect firefighters from hazardous combustion products. Water may be used to cool containers to prevent explosion of lids from pressure build-up.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode due to build-up of steam when exposed to extreme heat.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE
 CONDITIONS TO AVOID
 N/A

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Possible oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation of vapor or mist may cause headaches, nausea and irritation of the nose, throat or lungs.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Direct contact may cause a slight irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Prolonged or repeated contact may cause a slight skin irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

While this material has a low degree of toxicity, ingestion of excessive quantities may cause irritation of the digestive tract.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Ingestion and skin absorption: No evidence of adverse effects from available information. Inhalation: May be irritating to mucous membranes, respiratory tract and may produce symptoms of headache or nausea in poorly ventilated areas. Prolonged skin contact may cause reddening of the skin. Direct eye contact may cause eye irritation.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

This material has not been identified as a carcinogen by NTP, IARC or OSHA.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing lung conditions may be aggravated by exposure to this material.

EMERGENCY AND FIRST AID PROCEDURES

Swallowing: No harmful effects expected. Inhalation: No emergency care anticipated. Eyes and skin: Immediately flush eyes with water until water is no longer cloudy. Wash skin with soap and water until water is no longer cloudy. If clothing is soaked, remove and wash before reuse. Toxicology studies of similar materials have shown very low acute toxicity. There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Restrict area to cleanup personnel only. Major spills should be collected for disposal. Minor spills may be flushed into sewer if permitted by state, federal and local regulations.

WASTE DISPOSAL METHOD

Incinerate or bury in suitable landfill where permitted by appropriate government regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep containers cool and dry. Use and store this product with adequate ventilation. Keep product containers closed when not in use. Avoid subjecting this product to extreme temperature variations and freezing.

OTHER PRECAUTIONS

Do not store below 40 degrees fahrenheit.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Respiratory protection may be necessary to minimize exposure to vapors depending on the nature and concentration of the airborne material. Use a respirator with appropriate filters and cartridges (Niosh approved) or supplied air equipment.

VENTILATION

If current ventilation practices are not adequate to minimize exposure, additional ventilation or exhaust systems may be required.

PROTECTIVE GLOVES

Use gloves made of Neoprene, Butyl or natural rubber.

EYE PROTECTION

Use chemical splash goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

It is suggested that a source of clean water be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

WORK/HYGIENIC PRACTICES

After using this product, wash hands thoroughly before eating or smoking.

===== SECTION IX - DISCLAIMER =====

The information accumulate herein is believed to be accurate but is not warranted to be whether originating with Burke Industrial Coatings or not. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable for their circumstances. To our knowledge, this MSDS complies with 29CFR 1910, 1200.