

# PRIMELIFE-5150

<b>DESCRIPTION</b>	A high quality, fast dry, rust inhibitive aerosol metal primer.
<b>USES</b>	Use on most metal surfaces.
<b>APPEARANCE</b>	Flat red oxide.
<b>RECOMMENDED TOPCOATS</b>	Supercoat-316L, Overcoat-2020 or any BIC bulk product.
<b>PROPELLANT</b>	Propane Isobutane
<b>PHYSICAL PROPERTIES</b>	
CAN PRESSURE:	60 PSI @ 70°F.
ADHESION	Rate excellent
FLEXIBILITY	Full bend over 1/8" mandrel
TEMPERATURE RESISTANCE	300°F
DRY TIMES	@ 70°F - 80°F, (21° - 27°C) AND 50% RH
Dry to touch	10 minutes
Recoat	30 minutes
Hard cure	2 hours
<b>SAFETY INFORMATION</b>	
VOC (%)	60%
FLASH POINT	Aerosol - 10°F (T.O.C.)

For specific safety information refer to the **Material Safety Data Sheet**.

FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN

## PRODUCT ORDERING INFORMATION: PRIMELIFE-5150

Product number	Size	Wt./Case	Case Quantity
14-5150-00	16 oz. can	6.5 lb.	6
			(Sold only by case)

BURKE INDUSTRIAL COATINGS  
600 S. 74<sup>th</sup> Place, Suite 108, Ridgefield, WA 98642  
Tel: (360) 887-8819 Fax: (360) 887-8825  
Customer Service (800) 348-3245