

PRIMELIFE-5150

| | |
|-----------------------------|---|
| DESCRIPTION | A high quality, fast dry, rust inhibitive aerosol metal primer. |
| USES | Use on most metal surfaces. |
| APPEARANCE | Flat red oxide. |
| RECOMMENDED TOPCOATS | Supercoat-316L, Overcoat-2020 or any BIC bulk product. |
| PROPELLANT | Propane Isobutane |

PHYSICAL PROPERTIES

| | |
|------------------------|--|
| CAN PRESSURE: | 60 PSI @ 70°F. |
| ADHESION | Rate excellent |
| FLEXIBILITY | Full bend over 1/8" mandrel |
| TEMPERATURE RESISTANCE | 300°F |
| DRY TIMES | @ 70°F - 80°F, (21° - 27°C) AND 50% RH |
| Dry to touch | 10 minutes |
| Recoat | 30 minutes |
| Hard cure | 2 hours |

SAFETY INFORMATION

| | |
|-------------|-------------------------|
| VOC (%) | 60% |
| FLASH POINT | Aerosol - 10°F (T.O.C.) |

For specific safety information refer to the **Material Safety Data Sheet**.

FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN

PRODUCT ORDERING INFORMATION: PRIMELIFE-5150

| Product number | Size | Wt./Case | Case Quantity |
|----------------|------------|----------|--------------------------|
| 14-5150-00 | 16 oz. can | 6.5 lb. | 6 (Sold only by case) |

BURKE INDUSTRIAL COATINGS
600 S. 74th Place, Suite 108, Ridgefield, WA 98642
Tel: (360) 887-8819 Fax: (360) 887-8825
Customer Service (800) 348-3245